

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Trade Size

Trade Size

UNF605G Ocal 2" PVC CTD Female Union HZD Loc *Abb Installation Products, Inc*

Catalog Number	UNF605G
Manufacturer	Abb Installation Products, Inc
Description	PVC Coated Explosion and Dust-Ignition Proof Unf Female Union, Pipe Size 2 Inch/53 Metric, 3 Piece, For Hazardous and Non-Hazardous Locations, Overall Length 2.50 Inch/63.50 Millimeters, Overall Diameter 3.81 Inch/96.77 Millimeters,
	Electrogalvanized Steel, Gray
Weight per unit	
Product Category	Rigid Conduit Fittings - Steel
Features	
Material	Steel
outside diameter	3.8100000000000
Material, Color, and Finish	
Color	Gray
Dimensions and Weight	
Length	2.50000000000000
Descriptions	
Description	OCAL 2" PVC CTD FEMALE UNION HZD LOC
extra long description	ABB UNF605-G PVC CTD UNF FEM UNION
Long Description	PVC Coated Explosion and Dust-Ignition Proof UNF Female Unior Pipe Size 2 Inch/53 Metric, 3 Piece, for Hazardous and Non-hazardous Locations, Overall Length 2.50 Inch/63.50 Millimeters, Overall Diameter 3.81 Inch/96.77 Millimeters, Electrogalvanized Steel, Gray
Product Type	PVC CTD Unf Fem Union 2IN Gray
Special Features	Compact Design Which Permits Assembly with a Minimum of Clearance to Other Adjacent Conduit and/or Equipment
Manufacturer Information	
Brand	OCAL
GTIN	00704508413262
Manufacturers Part Number	UNF605G
UPC	704508413262
Taxonomies, Classifications, and G	Categories
Category Description	ALL DI ACTIDONID FITTINGO
Туре	Female Union
T 0'	

2 in



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pack	(ag	jin	g
	C_{α}	rta	n

Carton	6	
Weight Per each	4.32	

Uses, Certifications, and Standards

Application	To Connect Conduit to Conduit, or to Provide a Means for Future
	Modification of the Conduit System
standard	UL 1203, CSA