# Eaton V48M28T12EE

# Catalog Number: V48M28T12EE

General specifications

Eaton General purpose ventilated transformer, DT-3 (3-phase), PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 208Y/120V, 150°C rise w/ 200°C insulation systeam, 112.5 kVA, EE



Photo is representative

#### **Product Name** Catalog Number V48M28T12EE Eaton General purpose ventilated transformer UPC 786680019371 Product Length/Depth **Product Height** 32.02 in 23.42 in **Product Width Product Weight** 28.22 in 793 lb Compliances Warranty Eaton Selling Policy 25-000, one (1) year NEMA TP-1 Compliant from the date of installation of the Certifications Product or eighteen (18) months from the UL Listed date of shipment of the Product, whichever occurs first. **Catalog Notes** NEMA TP-1 efficient



# **Physical Attributes**

#### Coil material

Aluminum

Frame

916A

Tap size 2 at +2.5% FCAN, 4 at -2.5% FCBN

Type Dry Type Distribution Transformer

## Performance Ratings

Frequency rating

60 Hz

Primary voltage 480 V

Secondary Voltage 208 Y/120 V

Temperature rise

150 °C rise

Volt ampere rating

112.5 kVA

### Miscellaneous

Weathershield WS19

## Resources

Catalogs Eaton's Volume 2—Commercial Distribution

Specifications and datasheets Eaton Specification Sheet - V48M28T12EE



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia