



## **DOE 2016 Efficient Transformer**

V48M28T4516

UPC:786680147531

**Dimensions:** 

Height: 36.88 INLength: 21.13 INWidth: 24.88 IN

Weight:436 LB

Notes:10 CFR Part 431 (2016) Efficient

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

**Specifications:** 

Coil Material: Aluminum
Efficiency: DOE 2016
Enclosure: NEMA 2

• Frame: 940

• Frequency Rating: 60 Hz

Insulation: 220CKva Rating: 45 kVAPhase: Three-phase

Primary Voltage: 480V DeltaSecondary Voltage: 208Y/120

• Sound Level: 45 dB

• Tap Size: 2 at -2.5% FCAN, 4 at -2.5% FCBN

• Temperature Rating: 150°C rise

Weathershield: WS58Wiring Connection: 280B

**Supporting documents:** 

• Eaton Specification Sheet - V48M28T4516

**Certifications:** 

• UL Listed



## **Product compliance:**

• DOE2016 Efficient

\_\_\_\_\_

© 2016 Eaton. All rights reserved.





## **DOE 2016 Efficient Transformer**

V48M28T4516

UPC:786680147531

**Dimensions:** 

Height: 36.88 INLength: 21.13 INWidth: 24.88 IN

Weight:436 LB

Notes:10 CFR Part 431 (2016) Efficient

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

**Specifications:** 

Coil Material: Aluminum
Efficiency: DOE 2016
Enclosure: NEMA 2

• Frame: 940

• Frequency Rating: 60 Hz

Insulation: 220CKva Rating: 45 kVAPhase: Three-phase

Primary Voltage: 480V DeltaSecondary Voltage: 208Y/120

• Sound Level: 45 dB

• Tap Size: 2 at -2.5% FCAN, 4 at -2.5% FCBN

• Temperature Rating: 150°C rise

Weathershield: WS58Wiring Connection: 280B

**Supporting documents:** 

• Eaton Specification Sheet - V48M28T4516

**Certifications:** 

• UL Listed



## **Product compliance:**

• DOE2016 Efficient

\_\_\_\_\_

© 2016 Eaton. All rights reserved.