



DOE 2016 Efficient Transformer

V48M28T7516

UPC:786680147548

Dimensions:

Height: 43 INLength: 24 INWidth: 30.5 IN

Weight: 609 LB

Notes:10 CFR Part 431 (2016) Efficient

Warranties:

• Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

Coil Material: Aluminum
Efficiency: DOE 2016
Enclosure: NEMA 2

• Frame: 942

• Frequency Rating: 60 Hz

Insulation: 220CKva Rating: 75 kVAPhase: Three-phase

Primary Voltage: 480V DeltaSecondary Voltage: 208Y/120

• Sound Level: 50 dB

• Tap Size: 2 at +2.5% FCAN, 4 at -2.5% FCBN

• Temperature Rating: 150°C rise

Weathershield: WS59Wiring Connection: 280B

Supporting documents:

• Eaton Specification Sheet - V48M28T7516

Certifications:

• UL Listed



Product compliance:

• DOE2016 Efficient

© 2016 Eaton. All rights reserved.





DOE 2016 Efficient Transformer

V48M28T7516

UPC:786680147548

Dimensions:

Height: 43 INLength: 24 INWidth: 30.5 IN

Weight: 609 LB

Notes:10 CFR Part 431 (2016) Efficient

Warranties:

• Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

Coil Material: Aluminum
Efficiency: DOE 2016
Enclosure: NEMA 2

• Frame: 942

• Frequency Rating: 60 Hz

Insulation: 220CKva Rating: 75 kVAPhase: Three-phase

Primary Voltage: 480V DeltaSecondary Voltage: 208Y/120

• Sound Level: 50 dB

• Tap Size: 2 at +2.5% FCAN, 4 at -2.5% FCBN

• Temperature Rating: 150°C rise

Weathershield: WS59Wiring Connection: 280B

Supporting documents:

• Eaton Specification Sheet - V48M28T7516

Certifications:

• UL Listed



Product compliance:

• DOE2016 Efficient

© 2016 Eaton. All rights reserved.