Eaton V48M28T7516CU

Catalog Number: V48M28T7516CU

Eaton General purpose ventilated transformer, Fungus proof, CU windings, DOE 2016, NEMA 2, FR942, 220°C, 75 kVA, Floor/wall mnt upright only, 3-phase, PV: 480V delta, SV: 208Y/120, NEMA ST-20, 2 at +2.5%, 4 at -2.5%, 150°C, 75 kVA

General specifications

Product Name Eaton General purpose ventilated transformer

Product Length/Depth

24 in

Product Width 30.5 in

Warranty

Eaton Selling Policy 25-000, one (1) year DOE2016 Efficient from the date of installation of the Certifications Product or eighteen (18) months from the UL Listed date of shipment of the Product, whichever occurs first.

UPC 786680192012 **Product Height**

Catalog Number V48M28T7516CU

Product Weight 632 lb

Compliances

43 in

Catalog Notes 10 CFR Part 431 (2016) Efficient



Photo is representative



Physical Attributes

Coil material

Copper

Enclosure

NEMA 2

Frame

FR942

Insulation

220 °C

Material Copper windings

Mounting Floor or wall, upright only

Tap size 2 at +2.5%, 4 at -2.5%

Type Energy-efficient ventilated dry-type transformer

Wiring connection

280B

Performance Ratings

Efficiency

10 CFR Part 431-2016 (DOE 2016)

Frequency rating 60 Hz

Kva Rating

75 kVA

Primary voltage

480 V delta

Secondary Voltage 208Y/120 V

Sound Level NEMA ST-20

Temperature rise 150 °C rise

Volt ampere rating 75 kVA

Voltage rating 480 Vac-208Y/120 Vac

Resources

Brochures Eaton's low-voltage dry-type distribution transformers Eaton's high-efficiency dry-type transformers

Specifications and datasheets Eaton Specification Sheet - V48M28T7516CU

Warranty guides Selling Policy 25-000 - Distribution and Control Products and Services



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia