


# VAN3HH70QT

Medium size ceiling mount fixture: 35, 50 and 70 watt HPS, 50 and 70 watt Metal Halide. Housing is die cast aluminum with clear vandalproof polycarbonate refractor. Quartz Restrike models available. Lamps supplied.

Color: N/A

Weight: 11.6 lbs



## Lamp Info

Type: ED17  
Watts: 70W  
Shape/Size: N/A  
Base: N/A  
ANSI: N/A  
Hours: 15,000  
Lamp Lumens: 5,600  
Efficacy: 62 LPW

## Ballast Info

Type: HX-HPF QT  
120V: .7/.8A  
208V: .4/.45A  
240V: .35/.4A  
277V: .3/.35A  
Input Watts: 90W  
Efficiency: 78%

## Technical Specifications

### UL Listing:

Suitable for wet locations. Fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

### Sockets:

Medium base 4kv Pulse Rated Glazed porcelain.

### Refractor:

Injection molded polycarbonate, designed for maximum structural strength.

### HID Quartz restrike:

Add suffix "/QR" to Van3 (50w restrike) or Van5 (100w restrike) for HOT restrike. Provides immediate illumination in case of momentary power failure.

### Housings:

Die cast aluminum with powder coat bronze or white finish.

### Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER).

### Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel.

### Conduit Entry:

1/2".

### Quad Tap:

Fixture works with 120, 208, 240 and 277 Volts .

### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

### EISA 2007 Compliant:

This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008. Pulse Start offers Longer Lamp Life, Faster Startup and Faster Restrike.

### Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

### Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

### Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

### Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

### GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.




# VAN3HH70QT

Medium size ceiling mount fixture: 35, 50 and 70 watt HPS, 50 and 70 watt Metal Halide. Housing is die cast aluminum with clear vandalproof polycarbonate refractor. Quartz Restrike models available. Lamps supplied.

Color: N/A

Weight: 11.6 lbs



## Lamp Info

Type: ED17  
Watts: 70W  
Shape/Size: N/A  
Base: N/A  
ANSI: N/A  
Hours: 15,000  
Lamp Lumens: 5,600  
Efficacy: 62 LPW

## Ballast Info

Type: HX-HPF QT  
120V: .7/.8A  
208V: .4/.45A  
240V: .35/.4A  
277V: .3/.35A  
Input Watts: 90W  
Efficiency: 78%

## Technical Specifications

### UL Listing:

Suitable for wet locations. Fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

### Sockets:

Medium base 4kv Pulse Rated Glazed porcelain.

### Refractor:

Injection molded polycarbonate, designed for maximum structural strength.

### HID Quartz restrike:

Add suffix "/QR" to Van3 (50w restrike) or Van5 (100w restrike) for HOT restrike. Provides immediate illumination in case of momentary power failure.

### Housings:

Die cast aluminum with powder coat bronze or white finish.

### Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER).

### Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel.

### Conduit Entry:

1/2".

### Quad Tap:

Fixture works with 120, 208, 240 and 277 Volts .

### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

### EISA 2007 Compliant:

This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008. Pulse Start offers Longer Lamp Life, Faster Startup and Faster Restrike.

### Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

### Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

### Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

### Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

### GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

