Voice/Data/Video Tools

Ratcheting Crimper with Coaxial Hex-Crimp Die Set

VDV212-803

- *Professional CATV, Electrical, Home-Theater, Satellite and Security System crimper is perfect for fast, reliable connector installations.*
- *Precision full-cycle ratchet action assures complete precise crimp every cycle.*
- *Crimps meet or exceed UL Standards, where applicable.*
- *Steel body with black-oxide finish for corrosion resistance and durability.*
- *Preset tension for optimum performance.*
- *Dies manufactured from heat treated high-carbon steel for excellent performance and long life.*
- *Quick change interchangeable die-sets.*
- *Thumb-screws secure die-sets for quick easy changes. (Optional Phillips screws available, see table below.)*
- *Safety crimp release helps eliminate rejected terminations due to incorrect positioning.*
- *Ratchet mechanism is designed to prevent the release of the connector prior to full compression.*
- *Yellow and black grips enhance comfort, visibility, and allow quick identification.*

VDV212-034

Hex BNC Connector

Coax Cable

HEX F Connector

Cat. No.	Set Contains:					Overall Length	Weight (oz.)
VDV212-803						8.8" (224 mm)	21.0
	Cat. No.	***Description***	***Color***	***Nest Dimensions***	***Connector Type***		
	VDV212-034	hex crimp RG59/6 coaxial cable F-connectors	black	0.255"/0.320"/0.350" 6.48/8.13/8.89 mm	hex crimp BNC hex crimp F		

VDV200-010

VDV205-035

VDV205-036

VDV211-037

VDV211-038

VDV205-039

VDV999-033

VDV201-040

VDV211-041

VDV201-042

VDV211-043

VDV205-044

Cat. No.	Description	Nest Dimensions
VDV200-010	ratcheting crimper frame (yellow/black)	–
VDV999-033	replacement screw set (pair thumb and pair Phillips)	–
VDV212-034	hex crimp RG59/6 coaxial cable F-connectors	0.255"/0.320"/0.350" (6.48/8.13/8.89 mm)
VDV205-035	Insulated terminals, AWG 10-22	AWG 22-18/16-14/12-10 (DIN 0.5-1.0/1.5-2.5/4-6 mm^2)
VDV205-036	non-insulated terminal or open barrel terminal, AWG 10-20	AWG 20-18/16-14/12-10 (DIN 0.5-1/1.5-2.5/4-6 mm^2)
VDV211-037	hex crimp Connectors RG6/58/59/62 coaxial cable	0.256"/0.319"/0.068"/0.213" (6.50/8.10/1.73/5.41 mm)
VDV211-038	hex crimp RG58/59/62 coaxial cable	0.256"/0.068"/0.213" (6.50/1.73/5.41 mm)
VDV205-039	insulated pin terminal or non-insulated ferrules, AWG 12-22	AWG 22/20/18/16/14/12 (DIN 0.5/0.75/1.0/1.5/2.5/4 mm^2)
VDV201-040	RG58/59/62/174 coaxial cable and fiber optic	0.043"/0.068"/0.100"/0.137"/0.213"/0.255" (1.09/1.73/2.54/3.48/5.41/6.48 mm)
VDV211-041	RG58/59/62/6 coaxial cable	0.255"/0.213"/0.098"/0.068"/0.321" (6.48/5.41/2.49/1.73/8.15 mm)
VDV201-042	RG174/179/Belden 8218 coaxial cable and fiber optic	0.042"/0.068"/0.078"/0.128"/0.151"/0.178" (1.07/7.73/1.98/3.25/3.84/4.52 mm)
VDV211-043	RG8/11/174/179/213	0.100"/0.128"/0.429" (2.54/3.25/10.90 mm)
VDV205-044	non-insulated terminal, AWG 8-18	AWG 18-16/14/12-10/8 (DIN 0.75-1.5/2.54/4-6/10 mm^2)

All dimensions are in inches and (millimeters).

⚠WARNING: Read carefully and understand instructions before using this tool.

⚠WARNING: Always wear approved eye protection.

⚠WARNING: NOT insulated. Will NOT protect against electrical shock.

⚠WARNING: Never use on or near live electrical circuits.