



## Wiremold PRESSURE TYPE WIRE CONNECTOR

Part No. W30



Plugmold® Multioutlet Systems are available in a wide variety of lengths and fittings and in a variety of finishes to provide versatile solutions for many applications. Plugmold options include single or alternating circuits, standard or isolated ground receptacles, GFCI protection, tamper-resistant protection, USB charging, Snapicoil® harnesses of prewired receptacles, and cord-ended units. Plugmold® Multioutlet Systems are available in black or ivory ScuffCoat™ finish, painted white or gray enamel steel, stylish stainless steel, anodized aluminum and durable textured ivory nonmetallic. The painted steel product works with many types of decor and is paintable to integrate with most color schemes. Durable stainless steel and anodized aluminum Plugmold products are corrosion-resistant, making them ideal for labs.

### Features & Benefits

---

For common connection of two, three, or four No. 12 or No.14 solid copper conductors (White).

### Specifications

---

#### General Info

---

|                   |               |                |              |
|-------------------|---------------|----------------|--------------|
| Product Line      | Wiremold      | UPC Number     | 786776080810 |
| Country Of Origin | United States | Product Series | 2000 Series  |

---

|                    |   |          |  |
|--------------------|---|----------|--|
| Application Sector | Commercial, Education, Entertainment, Healthcare, Hospitality, Retail | Standard | cULus Listed<br>Base & Blank<br>Cover: File E4376<br>Guide RJBT.<br>Multioutlet<br>Assemblies: File<br>E15191 Guide<br>PVT. Fittings:<br>File E41751<br>Guide RJPR.<br>Base & Blank<br>Cover &<br>Plugmold Series<br>w/Snapcoil<br>Harness: Meets<br>Article 386 of<br>NEC. Meets<br>Section 12-3032<br>of CEC.<br>Plugmold Wired<br>Sections: Meets<br>Article 380 of<br>NEC. Meets<br>Section 12-3032<br>of CEC. |
|--------------------|---|----------|--|

|               |  |      |             |
|---------------|--|------|-------------|
| Warranty Type | 1-Year from Installation or 2-Years from Day of Sale | Type | Accessories |
|---------------|--|------|-------------|

### Dimensions

|                   |         |                   |           |
|-------------------|---------|-------------------|-----------|
| Product Weight US | 0.01 lb | Product Length US | 1.3125 in |
|-------------------|---------|-------------------|-----------|

### Listing Agencies / 3rd Party Agencies

|                     |        |              |     |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | E13382 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

### Trade Programs

|       |     |
|-------|-----|
| USMCA | Yes |
|-------|-----|

### Additional Information

|                |     |                               |     |
|----------------|-----|-------------------------------|-----|
| RoHS Compliant | Yes | Product Environmental Profile | Yes |
|----------------|-----|-------------------------------|-----|

### Technical Information

|          |      |                |        |
|----------|------|----------------|--------|
| Amperage | 20 A | Indoor/Outdoor | Indoor |
|----------|------|----------------|--------|

---

Voltage

300.0 V

Environmental Conditions

Dry interior  
locations

---



## Wiremold PRESSURE TYPE WIRE CONNECTOR

Part No. W30



Plugmold® Multioutlet Systems are available in a wide variety of lengths and fittings and in a variety of finishes to provide versatile solutions for many applications. Plugmold options include single or alternating circuits, standard or isolated ground receptacles, GFCI protection, tamper-resistant protection, USB charging, Snapicoil® harnesses of prewired receptacles, and cord-ended units. Plugmold® Multioutlet Systems are available in black or ivory ScuffCoat™ finish, painted white or gray enamel steel, stylish stainless steel, anodized aluminum and durable textured ivory nonmetallic. The painted steel product works with many types of decor and is paintable to integrate with most color schemes. Durable stainless steel and anodized aluminum Plugmold products are corrosion-resistant, making them ideal for labs.

### Features & Benefits

---

For common connection of two, three, or four No. 12 or No.14 solid copper conductors (White).

### Specifications

---

#### General Info

---

|                   |               |                |              |
|-------------------|---------------|----------------|--------------|
| Product Line      | Wiremold      | UPC Number     | 786776080810 |
| Country Of Origin | United States | Product Series | 2000 Series  |

---

|                    |   |          |  |
|--------------------|---|----------|--|
| Application Sector | Commercial, Education, Entertainment, Healthcare, Hospitality, Retail | Standard | cULus Listed<br>Base & Blank<br>Cover: File E4376<br>Guide RJBT.<br>Multioutlet<br>Assemblies: File<br>E15191 Guide<br>PVT. Fittings:<br>File E41751<br>Guide RJPR.<br>Base & Blank<br>Cover &<br>Plugmold Series<br>w/Snapcoil<br>Harness: Meets<br>Article 386 of<br>NEC. Meets<br>Section 12-3032<br>of CEC.<br>Plugmold Wired<br>Sections: Meets<br>Article 380 of<br>NEC. Meets<br>Section 12-3032<br>of CEC. |
|--------------------|---|----------|--|

|               |  |      |             |
|---------------|--|------|-------------|
| Warranty Type | 1-Year from Installation or 2-Years from Day of Sale | Type | Accessories |
|---------------|--|------|-------------|

### Dimensions

|                   |         |                   |           |
|-------------------|---------|-------------------|-----------|
| Product Weight US | 0.01 lb | Product Length US | 1.3125 in |
|-------------------|---------|-------------------|-----------|

### Listing Agencies / 3rd Party Agencies

|                     |        |              |     |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | E13382 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

### Trade Programs

|       |     |
|-------|-----|
| USMCA | Yes |
|-------|-----|

### Additional Information

|                |     |                               |     |
|----------------|-----|-------------------------------|-----|
| RoHS Compliant | Yes | Product Environmental Profile | Yes |
|----------------|-----|-------------------------------|-----|

### Technical Information

|          |      |                |        |
|----------|------|----------------|--------|
| Amperage | 20 A | Indoor/Outdoor | Indoor |
|----------|------|----------------|--------|

---

Voltage

300.0 V

Environmental Conditions

Dry interior  
locations

---