

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



WL5 Wire Pulling Lubricant Gel, 5 Gallons *Minnesota Mining (3M)*

Catalog Number	WL5
Manufacturer	Minnesota Mining (3M)
Description	3M™ Wire Pulling Lubricant WL Is A Translucent Polymer Gel That Acts As An Excellent Lubricant For Pulling Both Electrical and Communication Cable. This Lubricant Gel Wipes Off The Cable
	Quickly and Cleanly Before Terminating or Splicing. The Lubricant Has A Low Coefficient Of Friction Which Lessens The Chance Of Cable Jacket Damage From High Pulling Forces.
Weight per unit	46.0 (lbs/each)
Product Category	Paint, Chemicals, Etc.
Descriptions	
Description	WIRE PULLING LUBRICANT GEL, 5 GALLONS
extra long description	3M 7000031543 3M™ Wire-Pulling Lubr
Features	3M™ Wire Pulling Lubricant WL is a consistent gel that does not
	liquefy, or separate with hot or cold aging. It stays thick, smooth
	and ready to apply. Temperature range of 20 to 110 degrees F
	(-6.7 to 43 degrees C).
Long Description	3M™ Wire Pulling Lubricant WL is a translucent polymer gel that
	acts as an excellent lubricant for pulling both electrical and communication cable. This lubricant gel wipes off the cable
	quickly and cleanly before terminating or splicing. The lubricant
	has a low coefficient of friction which lessens the chance of cable
	jacket damage from high pulling forces.
Product Type	3M™ Wire-Pulling Lubricant WL
Special Features	Translucent White
Manufacturer Information	
Brand	3M
GTIN	00054007506249
Manufacturers Part Number	WL-5
UPC	054007506249
Taxonomies, Classifications, and Category Description	Categories ADHESIVES
Type	Gel
Packaging	
Carton	1
Weight Per each	46
Uses, Certifications, and Standard	ds
Application	Lubricant