



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

12555 Harris Branch Pkwy Suite 105
78653-0000, TX Manor
Phone: 512-339-8750
Fax: 512-339-6732



WL5 Wire Pulling Lubricant Gel, 5 Gallons *Minnesota Mining (3M)*

Catalog Number	WL5
Manufacturer	Minnesota Mining (3M)
Description	3M™ Wire Pulling Lubricant WL Is A Translucent Polymer Gel That Acts As An Excellent Lubricant For Pulling Both Electrical and Communication Cable. This Lubricant Gel Wipes Off The Cable Quickly and Cleanly Before Terminating or Splicing. The Lubricant Has A Low Coefficient Of Friction Which Lessens The Chance Of Cable Jacket Damage From High Pulling Forces.
Weight per unit	46.0 (lbs/each)
Product Category	Paint, Chemicals, Etc.

Descriptions

Description	WIRE PULLING LUBRICANT GEL, 5 GALLONS
extra long description	3M 7000031543 3M™ Wire-Pulling Lubr
Features	3M™ Wire Pulling Lubricant WL is a consistent gel that does not liquefy, or separate with hot or cold aging. It stays thick, smooth and ready to apply. Temperature range of 20 to 110 degrees F (-6.7 to 43 degrees C).
Long Description	3M™ Wire Pulling Lubricant WL is a translucent polymer gel that acts as an excellent lubricant for pulling both electrical and communication cable. This lubricant gel wipes off the cable quickly and cleanly before terminating or splicing. The lubricant has a low coefficient of friction which lessens the chance of cable jacket damage from high pulling forces.
Product Type	3M™ Wire-Pulling Lubricant WL
Special Features	Translucent White

Manufacturer Information

Brand	3M
GTIN	00054007506249
Manufacturers Part Number	7000031543
UPC	054007506249

Taxonomies, Classifications, and Categories

Category Description	ADHESIVES
Type	Gel

Packaging

Carton	1
Weight Per each	46

Uses, Certifications, and Standards

Application	Lubricant
-------------	-----------