ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685



WP3LED55 *DELISTED* 55W LED WALLPK 50K BRZ

RAB LIGHTING

Catalog Number	WP3LED55
Manufacturer	RAB LIGHTING
Description	LED Wallpack, Die-Cast Aluminum;Borosilicate Glass (Lens) Material, Bronze, 17 in Length, 10 in Width, 9 in Height, 100000 h Average Life, 5 yr Warranty, 16.8 lb
Weight per unit	16.8 (lbs/each)
Product Category	Led Wallpacks

Features

Voltage Rating	120/277
Wattage	55
Lumens	7026

Descriptions

Description	*DELISTED* 55W LED WALLPK 50K BRZ
Long Description	00198133067421|0001981|00198133067421|19813306742|06742|WP3I Lght WP3LED55|RAB Lighting WP3LED55|RAB WP3LED55|RAB-LAMP WP3LED55|RABLIGHTING WP3LED55|20332797
Product Type	Wal 55W Cool 120-277 With Glas
Extra Long Description	RAB WP3LED55 WAL 55W COOL 120-277 W

Manufacturer Information

GTIN	00019813306742
UPC	885360

Taxonomies, Classifications, and Categories

Category Description	LED FLOODLIGHTS, WALLPACKS, BOLLARDS & LANDSCAPE LIGHTING
Type	LED WALLPACKS

Availability

Manufacturer Status	Inactive

Packaging

Carton	1
Weight Per Each	16.8 (lbs/each)

WP3LED55

RAB Outdoor



Available in 55W, 65W, 82W, and 110W models with up to 15,531 lumens and 144 LPW. Covered by RAB's 5-year, no-compromise warranty.

Color: Bronze

Weight: 16.8 lbs

Project:	Type:
Prepared By:	Date:

Driver Info

Type:	Constant Current
120V:	0.46A
208V:	0.29A
240V:	0.25A
277V:	0.22A
Input Watts:	57W
Efficiency:	96%

LED Info

Watts:	55W
Color Temp:	5000K (Cool)
Color Accuracy:	82 CRI
L70 Lifespan:	100,000
Lumens:	7,026
Efficacy:	123 LPW

Technical Specifications

Listings

UL Listing:

Suitable for wet locations. Wall mount only.

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.
DLC Product Code: PYA29GUW

Electrical

Driver:

Constant Current, Class 2, 1400mA, 50/60 Hz. 100 - 277V, 4kV surge protection

Optical

BUG Rating:

B1 U4 G4

Construction

Thermal Management:

Superior thermal management with die-cast aluminum heatsink

Maximum Ambient Temperature:

Suitable for use in 40°C (104°F)

Cold Weather Starting:

Minimum starting temperature is -40°C (-40°F)

Housing:

Precision die-cast aluminum housing

Mounting:

Die-cast backbox with four (4) conduit entry points and knockout pattern for junction box or direct wall mounting. Hinged door for easy re-assembly.

Lens:

Prismatic, heat-resistant borosilicate glass

Reflector:

High-gloss white aluminum

Gaskets:

High-temperature silicone gaskets

Finish:

Formulated for high-durability and long lasting color

Green Technology:

Mercury and UV-free. RoHS compliant components.

LED Characteristics

Color Stability:

LED color temperature is warrantied to shift no more than 200K in CCT over a 5 year period

Color Uniformity:

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Other

Equivalency:

Equivalent to 400W Metal Halide

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions

Features

- Affordable wallpack with traditional look
- Covers footprint of traditional HID wallpacks
- Optional photocell (button or swivel) available
- 480V models available

Copyright © 2018 RAB Lighting Inc. All Rights Reserved Note: Specifications are subject to change at any time without notice

Ordering Matrix

Family	Wattage	Color Temp	Finish	Driver Options	Photocell Options
WP3LED	55	^	^	^	^
	55 = 55W **65** = 65W **82** = 82W **110** = 110W	**Blank** = 5000K (Cool) **Y** = 3000K (Warm) **N** = 4000K (Neutral)	**Blank** = Bronze **W** = White	**Blank** = 120-277V **/480** = 480V **/D10** = 0-10V Dimming **/480/D10** = 480V, 0-10V Dimming	**Blank** = No Option **/PC** = 120V Button **/PCS** = 120V Swivel **/PC2** = 277V Button **/PCS2** = 277V Swivel **/PCS4** = 480V Swivel

Copyright © 2018 RAB Lighting Inc. All Rights Reserved Note: Specifications are subject to change at any time without notice