

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



WT6B Wiretwist Wire Connector, WT6 Red, 250/Bag

Catalog Number	WT6B
Manufacturer	Ideal
Description	Buchanan, Wire Connector, Wiretwist, Conductor Range: 18 - 8 Awg, 2/14 Awg Min, 4/12 Awg Max, Number Of Conductors: 1 to 5, Material: Flame-Retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UI 94V-2 Flame-Retardant Shell Rated At 105 Deg C (221 F), Model Number: WT6
Weight per unit	0.0060 (lbs/each)
Product Category	Electrical Fixture Conn (Nuts
Features	
Material	Flame-retardant Polypropelene
Voltage Rating	600
Material, Color, and Finish Color	Red



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Description WIRETWIST WIRE CONNECTOR, WT6 RD, 250/BAG extra long description IDEAL WT6-B WIRE-TWIST CONN., RED, BA Features With five, color-coded connectors designed to accommodate hundreds of different solid or stranded wire combinations, WireTwist Wire Connectors offer an economical connector that brings a lot of value in comfort and performance. The fixed, live-action, square-wire spring threads itself as it draws wires into the connector, creating a secure pressure environments. The deep, wide-throated skirt protects against flashover and turned back strands providing Long Description Buchanan, Wire Connector, WireTwist, Conductor Range: 18 - 8 AWG, 2/14 AWG MIn, 4/12 AWG MAX, Number Of Conductors: 1 to 5, Material: Flame-retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Wire-Twist Conn., Red, Bag 250 Special Features 1,000V Maximum In Fixtures And Signs:Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection; Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip:Model Number: WT6:Ribbed Cap Provides Positive Grip For Fast, Easy Installation:Tough, UL 94V-2 Flame-Retardant Shell Manufacturer Information Barand Buchanan Grip:Model Number: WT6:Ribbed Cap Provides Positive Grip For Fast, Easy Installation:Tough, UL 94V-2 Flame-Retardant Shell Manufacturer Positive Grip For Fast, Easy Installation:Tough, UL 94V-2 Flame-Retardant Shell Manufact	Descriptions	
Features With five, color-coded connectors designed to accommodate hundreds of different solid or stranded wire combinations, WireTwist Wire Connectors offer an economical connector that brings a lot of value in comfort and performance. The fixed, live-action, square-wire spring threads itself as it draws wires into the connector, creating a secure pressure grip. The rugged, thermoplastic shell with stands extreme environments. The deep, wide-throated skirt protects against flashover and turned back strands providing Long Description Buchanan, Wire Connector, WireTwist, Conductor Range: 18 - 8 AWG, 2/14 AWG Min, 4/12 AWG MAX, Number Of Conductors: 1 to 5, Material: Flame-retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Wire-Twist Conn., Red, Bag 250 Special Features 1,000V Maximum In Fixtures And Signs:Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection:Features: Five Color-Coded Models Cover Common Construction Wire Ranges,Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip:Model Number: WT6 (Bibbed Cap Provides Positive Grip For Fast, Easy Installation:Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F):UL 486C Listed And CSA 22.2 #188 Certified Manufacturer Information Buchanan Grip Guranan Grip Model Number UPC 781789610092 Taxonomies, Classifications, and Categories Category Description Category Description <td>-</td> <td></td>	-	
hundreds of different solid or stranded wire combinations, WireTwist Wire Connectors offer an economical connector that brings a lot of value in comfort and performance. The fixed, live-action, square-wire spring threads itself as it draws wires into the connector, creating a secure pressure grip. The rugged, thermoplastic shell withstands extreme environments. The deep, wide-throated skirt protects against flashover and turned back strands providing Long Description Buchanan, Wire Connector, WireTwist, Conductor Range: 18 - 8 AWG, 2/14 AWG Min, 4/12 AWG MAX, Number Of Conductors: 1 to 5, Materiai: Flame-retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Wire-Twist Conn., Red, Bag 250 Special Features 1,000V Maximum In Fixtures And Signs, Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features, Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip:Model Number: WT6, Nitro Bubed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);	o 1	
Wire Twist Wire Connectors offer an economical connector that brings a lot of value in comfort and performance. The fixed, live-action, square-wire spring threads itself as it draws wires into the connector, creating a secure pressure grip. The rugged, thermoplastic shell withstands extreme environments. The deep, wide-throated skirt protects against flashover and turned back strands providing Long Description Buchanan, Wire Connector, WireTwist, Conductor Range: 18 - 8 AWG, 2/14 AWG Min, 4/12 AWG MAX, Number Of Conductors: 1 to 5, Material: Flame-retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Wire-Twist Conn., Red, Bag 250 Special Features 1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Flve Color-Coded Models Cover Common Construction Wire Range;Fiked, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip:Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation:Tough, UL 94V-2; Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA	reatures	о С
brings a lot of value in comfort and performance. The fixed, live-action, square-wire spring threads itself as it draws wires into the connector, creating a secure pressure grip. The rugged, thermoplastic shell withstands extreme environments. The deep, wide-throated skirt protects against flashover and turned back strands providing Long Description Buchanan, Wire Connector, WireTwist, Conductor Range: 18 - 8 AWG, 2/14 AWG Min, 4/12 AWG MAX, Number Of Conductors: 1 to 5, Material: Flame-retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Wire-Twist Conn., Red, Bag 250 Special Features 1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation:Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 Certified Manufacturer Information Brand Buchanan GTIN 00781789610092 Taxonomies, Classifications, and Categories Category Description WiRE NUTS Availability minimum qty 250		
live-action, square-wire spring threads itself as it draws wires into the connector, creating a secure pressure grip. The rugged, thermoplastic shell withstands extreme environments. The deep, wide-throated skirt protects against flashover and turned back strands providing Long Description Buchanan, Wire Connector, WireTwist, Conductor Range: 18 - 8 AWG, 2/14 AWG Min, 4/12 AWG MAX, Number Of Conductors: 1 to 5, Material: Flame-retardant Polypropetene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Wire-Twist Conn., Red, Bag 250 Special Features 1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges:Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip:Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 Certified Manufacturer Information Buchanan Rarad Buchanan GTIN 00781789610092 Manufacturers Part Number WT6-B UPC 781789610092 Taxonomies, Classifications, and Categories Category Description WIRE NUTS Availability minimum qty 250		
the connector, creating a secure pressure grip. The rugged, thermoplastic shell withstands extreme environments. The deep, wide-throated skirt protects against flashover and turned back strands providing Long Description Buchanan, Wire Connector, WireTwist, Conductor Range: 18 - 8 AWG, 2/14 AWG Min, 4/12 AWG MAX, Number Of Conductors: 1 to 5, Material: Flame-retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Wire-Twist Conn., Red, Bag 250 Special Features 1,000V Maximum In Fixtures And Signs:Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip:Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation:Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F):UL 486C Listed And CSA 22.2 #188 Certified Manufacturer Information Buchanan Brand Buchanan GTIN 00781789610092 Manufacturers Part Number WT6-B UPC 781789610092 Manufacturers Part Number WIRE NUTS Availability wiRE NUTS Availability 250		•
Image: strain of the second strain of the		
strands providing strands providing Long Description Buchanan, Wire Connector, WireTwist, Conductor Range: 18 - 8 AWG, 2/14 AWG Min, 4/12 AWG MAX, Number Of Conductors: 1 to 5, Material: Flame-retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Wire-Twist Conn., Red, Bag 250 Special Features 1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6/Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 Certified Manufacturer Information Brand Buchanan GTIN 00781789610092 Manufacturers Part Number WT6-B UPC 781789610092 Taxonomies, Classifications, and Categories Category Description QuPC 781789610092 Taxonomies, Classifications, and Categories Category Description WIRE NUTS Availability minimum qty 250		
Long DescriptionBuchanan, Wire Connector, WireTwist, Conductor Range: 18 - 8 AWG, 2/14 AWG Min, 4/12 AWG MAX, Number Of Conductors: 1 to 5, Material: Flame-retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6Product TypeWire-Twist Conn., Red, Bag 250Special Features1,000V Maximum In Fixtures And Signs:Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip:Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 CertifiedManufacturer InformationBuchanan GTINBrandBuchanan GTINUPC781789610092Taxonomies, Classifications, and Categories Category DescriptionWiRE NUTSAvailability minimum qty250		wide-throated skirt protects against flashover and turned back
AWG, 2/14 AWG Min, 4/12 AWG MAX, Number Of Conductors: 1 to 5, Material: Flame-retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Special Features 1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 Certified Manufacturer Information Brand Buchanan GTIN 00781789610092 Manufacturers Part Number WT6-B UPC 781789610092 Taxonomies, Classifications, and Categories Category Description WIRE NUTS Availability 250		strands providing
to 5, Material: Flame-retardant Polypropelene, Color: Red, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Wire-Twist Conn., Red, Bag 250 Special Features 1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 Certified Manufacturer Information Brand Buchanan GTIN 00781789610092 Manufacturers Part Number WT6-B UPC 781789610092 Taxonomies, Classifications, and Categories Category Description WIRE NUTS Availability minimum qty 250	Long Description	Buchanan, Wire Connector, WireTwist, Conductor Range: 18 - 8
Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6.Product TypeWire-Twist Conn., Red, Bag 250Special Features1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 CertifiedManufacturer InformationBuchanan GTINBrandBuchanan GTINUPC781789610092Manufacturers Part NumberWT6-B UPCUPC781789610092Taxonomies, Classifications, and Categories Category DescriptionWIRE NUTSAvailability minimum qty250		
94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT6 Product Type Wire-Twist Conn., Red, Bag 250 Special Features 1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 Certified Manufacturer Information Buchanan GTIN 00781789610092 Manufacturers Part Number WT6-B UPC 781789610092 Taxonomies, Classifications, and Categories Category Description WIRE NUTS Availability 250		
Number: WT6Product TypeWire-Twist Conn., Red, Bag 250Special Features1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 CertifiedManufacturer Information Brand GTINBuchanan O0781789610092Manufacturers Part NumberWT6-B UPCTaxonomies, Classifications, and Categories Category DescriptionWIRE NUTSAvailability minimum qty250		
Product TypeWire-Twist Conn., Red, Bag 250.Special Features1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 CertifiedManufacturer Information GTINBuchanan 00781789610092Manufacturers Part NumberWT6-B UPCUPC781789610092Taxonomies, Classifications, and Categories Category DescriptionWIRE NUTSAvailability minimum qty250		
Special Features1,000V Maximum In Fixtures And Signs;Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 CertifiedManufacturer Information Brand GTINBuchanan 00781789610092Manufacturers Part Number UPCWT6-B 781789610092Taxonomies, Classifications, and Categories Category DescriptionWIRE NUTSAvailability minimum qty250	Product Type	
Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 CertifiedManufacturer Information Brand GTIN UPCBuchanan 00781789610092 781789610092Taxonomies, Classifications, and Categories Category DescriptionWIRE NUTSAvailability minimum qty250	5.	0
Maximum Dielectric Protection;Features: Five Color-Coded Models Cover Common Construction Wire Ranges;Fixed, Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 CertifiedManufacturer Information Brand GTIN UPCBuchanan O0781789610092 781789610092Taxonomies, Classifications, and Categories Category DescriptionWT6-B WIRE NUTSAvailability minimum qty250	special reactines	
Square-Wire Spring Threads Itself Creating A Secure Pressure Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 CertifiedManufacturer Information Brand GTINBuchanan 00781789610092Manufacturers Part Number UPCWT6-B 781789610092Taxonomies, Classifications, and Categories Category DescriptionWIRE NUTSAvailability minimum qty250		•
Grip;Model Number: WT6;Ribbed Cap Provides Positive Grip For Fast, Easy Installation;Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 CertifiedManufacturer InformationBuchanan 00781789610092GTIN00781789610092Manufacturers Part NumberWT6-B UPCTaxonomies, Classifications, and Categories Category DescriptionAvailability minimum qty250		Models Cover Common Construction Wire Ranges; Fixed,
Fast, Easy Installation; Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F); UL 486C Listed And CSA 22.2 #188 Certified Manufacturer Information Brand Buchanan GTIN 00781789610092 Manufacturers Part Number WT6-B UPC 781789610092 Taxonomies, Classifications, and Categories Category Description WIRE NUTS Availability 250		Square-Wire Spring Threads Itself Creating A Secure Pressure
Rated At 105 Degree C (221 Degree F);UL 486C Listed And CSA 22.2 #188 CertifiedManufacturer InformationBuchanan 00781789610092GTIN00781789610092Manufacturers Part NumberWT6-B UPCUPC781789610092Taxonomies, Classifications, and Categories Category DescriptionWIRE NUTSAvailability minimum qty250		
22.2 #188 CertifiedManufacturer InformationBrandBuchananGTIN00781789610092Manufacturers Part NumberWT6-BUPC781789610092Taxonomies, Classifications, and CategoriesCategory DescriptionWIRE NUTSAvailability250		
Manufacturer InformationBrandBuchananGTIN00781789610092Manufacturers Part NumberWT6-BUPC781789610092Taxonomies, Classifications, and CategoriesCategory DescriptionWIRE NUTSAvailabilityminimum qty250		
BrandBuchananGTIN00781789610092Manufacturers Part NumberWT6-BUPC781789610092Taxonomies, Classifications, and CategoriesCategory DescriptionWIRE NUTSAvailability250		22.2 #188 Certified
GTIN00781789610092Manufacturers Part NumberWT6-BUPC781789610092Taxonomies, Classifications, and CategoriesCategory DescriptionWIRE NUTSAvailability250		
Manufacturers Part NumberWT6-BUPC781789610092Taxonomies, Classifications, and CategoriesCategory DescriptionWIRE NUTSAvailability250		
UPC781789610092Taxonomies, Classifications, and Categories Category DescriptionKategory DescriptionWIRE NUTSAvailability minimum qty250		
Taxonomies, Classifications, and Categories Category DescriptionCategory DescriptionWIRE NUTSAvailability minimum qty250		
Category Description WIRE NUTS Availability minimum qty 250		
Availability minimum qty 250		
minimum qty 250	Category Description	WIRE NUTS
	Availability	
Packaging	minimum qty	250
	Packaging	
Carton 5000		5000
Weight Per each 0.006	Weight Per each	0.006



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Insulating or Joining 1 or more conductors
environmental conditions	Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221
standard	CSA C22.2 #188, UL 486C Listed, RoHS