

TECHNICAL DATA SHEET

# **Fittings, Armored Cable/Flexible Metallic Conduit** Squeeze type fittings - XC series

# **Steel City®**



#### **Applications:**

- For indoor use only
- Electrical enclosures
- Knockouts (locknut included)
- Threaded entries

#### **Conformance:**

- UL File No. E-1383: 3/8" 3/4"
- UL File No. E-23018: All sizes
- CSA File No. 601176

Squeeze Type Fitting for attachment of Armored Cable or Flexible metallic conduits to electrical enclosures. Commercial and Industrial applications.

## **Certifications / Standards:**





#### **Connection Type:**

- Squeeze Type
- Tri combo head screws for fittings under 2
- Hexagonal head and tri combo drive screws for fittings 2" and larger
- Non-insulated: XC-40\* series
- Insulated: XC-90\* series

## Materials / Finishes:

- Malleable Iron
- Steel zinc plated

Technical data sheet   TDS000226 B
Fittings, Armored Cable/Flexible Metallic Conduit

Product selection (inches)											
Part No.	Туре	Conduit size	А	В	С	D	Threads	Throat Dia. w/ insulator	Throat Dia. w/o insulator	SCREW SIZE	
XC-400	1	3/8	1.10	.90	.66	1.00	½ -14 npsm	N/A	.35	#8-32 UNC	
XC-401 / XC-901	2	1/2	1.52	1.69	.97	1.22	½ -14 npsm	.55	.59	#10-32 UNC	
XC-402 / XC-902	2	3/4	1.46	1.93	1.17	1.38	³/₄ -14 npsm	.75	.76	#10-32 UNC	
XC-403 / XC-903	2	1	1.68	2.39	1.46	1.72	1 -11.5 npsm	.96	.98	#10-32 UNC	
XC-404 / XC-904	3	11/4	1.80	2.63	1.75	2.00	1¼ -11.5 npsm	1.20	1.21	#12-24 UNC	
XC-405 / XC-905	3	11/2	2.46	2.90	2.01	2.29	1½ -11.5 npsm	1.37	1.47	#12-24 UNC	
XC-406 / XC-906	3	2	2.76	3.49	2.52	2.82	2 – 11.5 npsm	1.82	1.92	#12-24 UNC	
XC-407 / XC-907	3	21/2	3.00	4.08	3.13	3.45	2½ - 8 npsm	2.30	2.40	#12-24 UNC	
XC-408 / XC-908	3	3	3.19	4.89	3.64	3.96	3 – 8 npsm	2.93	2.98	#12-24 UNC	

 $Note: Product\ must\ be\ installed\ in\ accordance\ with\ applicable\ national\ and\ local\ electrical\ codes.$ 

Type 1 Type 2 Type 3

















