

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## XHHW250YLPCS AI XHHW 250 STR Yellow PCS

Catalog Number       XHHW250YLPCS         Manufacturer       King Wire Inc.         Description       Aluminum Building Wire, Abrasion, Moisture, Heat and Sunlight Resistant Insulation; Cable Can Be Installed Without Pulling Lubricant Additional Information, General Purpose Wiring Application, Yellow Color, Aluminum Conductor Material, 250 MCM Conductor Size, 230 A Current Rating, Polyethylene Insulation Material, 65 Mil Insulation Thickness, Made In Usa, +90 °C Maximum Operating Temperature, 37 - Strands, 0.655 In Outside Diameter, 1000 FT Overall Length, Carton Package Type, Directive 2002/95/Ec;Federal S         Weight per unit       0.2930 (lbs/ft)         Product Category       XHHW 250 STR YELLOW PCS         Manufacturer Information Brand       Aluminum         Taxonomies, Classifications, and Categories Category Description       AL XHHW 250 STR YELLOW PCS         Packaging Carton       1         Weight Per foot       0.293	King Wire Inc.	
Description       Aluminum Building Wire, Abrasion, Moisture, Heat and Sunlight Resistant Insulation;Cable Can Be Installed Without Pulling Lubricant Additional Information, General Purpose Wiring Application, Yellow Color, Aluminum Conductor Material, 250 MCM Conductor Size, 230 A Current Rating, Polyethylene Insulation Material, 65 Mil Insulation Thickness, Made In Usa, +90 °C Maximum Operating Temperature, 37 - Strands, 0.655 In Outside Diameter, 1000 FT Overall Length, Carton Package Type, Directive 2002/95/Ec;Federal S         Weight per unit       0.2930 (lbs/ft)         Product Category       XHHW-STR (Stranded)         Descriptions       AL XHHW 250 STR YELLOW PCS         Manufacturer Information       Aluminum         Brand       Aluminum         Taxonomies, Classifications, and Categories Category Description       ALUM BUILDING WIRE         Packaging Carton       1	Catalog Number	XHHW250YLPCS
Resistant Insulation;Cable Can Be Installed Without Pulling Lubricant Additional Information, General Purpose Wiring Application, Yellow Color, Aluminum Conductor Material, 250 MCM Conductor Size, 230 A Current Rating, Polyethylene Insulation Material, 65 Mil Insulation Thickness, Made In Usa, +90 °C Maximum Operating Temperature, 37 - Strands, 0.655 In Outside Diameter, 1000 FT Overall Length, Carton Package Type, Directive 2002/95/Ec;Federal SWeight per unit Product Category0.2930 (lbs/ft) XHHW-STR (Stranded)Descriptions DescriptionAL XHHW 250 STR YELLOW PCSManufacturer Information BrandAluminumTaxonomies, Classifications, and Categories Category DescriptionALUM BUILDING WIREPackaging Carton1	Manufacturer	King Wire Inc.
Product Category       XHHW-STR (Stranded)         Descriptions       AL XHHW 250 STR YELLOW PCS         Manufacturer Information       Aluminum         Brand       Aluminum         Taxonomies, Classifications, and Categories       Category Description         Category Description       ALUM BUILDING WIRE         Packaging       1	Description	Resistant Insulation;Cable Can Be Installed Without Pulling Lubricant Additional Information, General Purpose Wiring Application, Yellow Color, Aluminum Conductor Material, 250 MCM Conductor Size, 230 A Current Rating, Polyethylene Insulation Material, 65 Mil Insulation Thickness, Made In Usa, +90 °C Maximum Operating Temperature, 37 - Strands, 0.655 In Outside Diameter, 1000 FT Overall Length, Carton Package Type,
Descriptions       AL XHHW 250 STR YELLOW PCS         Manufacturer Information       Aluminum         Brand       Aluminum         Taxonomies, Classifications, and Categories       Category Description         Category Description       ALUM BUILDING WIRE         Packaging       1	Weight per unit	0.2930 (lbs/ft)
Description       AL XHHW 250 STR YELLOW PCS         Manufacturer Information       Brand         Brand       Aluminum         Taxonomies, Classifications, and Categories       Category Description         Category Description       ALUM BUILDING WIRE         Packaging       1	Product Category	XHHW-STR (Stranded)
Manufacturer Information         Brand       Aluminum         Taxonomies, Classifications, and Categories         Category Description       ALUM BUILDING WIRE         Packaging         Carton       1	Descriptions	
BrandAluminumTaxonomies, Classifications, and Categories Category DescriptionCategory DescriptionALUM BUILDING WIREPackaging Carton1	•	AL XHHW 250 STR YELLOW PCS
Taxonomies, Classifications, and Categories         Category Description       ALUM BUILDING WIRE         Packaging       I         Carton       1	Manufacturer Information	
Category Description ALUM BUILDING WIRE Packaging Carton 1	Brand	Aluminum
Category Description ALUM BUILDING WIRE Packaging Carton 1	Taxonomies, Classifications, and C	categories and the second s
Carton 1		•
Carton 1	Packaging	
Weight Per foot 0.293		
	Weight Per foot	0.293