

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



XHHW750PCS AI XHHW 750 STR Black PCS

King Wire Inc.

| Catalog Number | XHHW750PCS | | |
|------------------------|--|--|--|
| Manufacturer | King Wire Inc. | | |
| Description | Aluminum Building Wire, Abrasion, Moisture, Heat and Sunlight Resistant Insulation; Cable Can Be Installed Without Pulling Lubricant Additional Information, General Purpose Wiring Application, Black, Aluminum Conductor Material, 750 MCM Conductor Size, 435 A Current Rating, Polyethylene Insulation Material, 80 Mil Insulation Thickness, Made In Usa, +90 °C Maximum Operating Temperature, 61 - Strands, 1.075 In Outside Diameter, 1000 FT Overall Length, Carton Package Type, Directive 2002/95/Ec;Federal Specific | | |
| Weight per unit | 0.8240 (lbs/ft) | | |
| Product Category | XHHW-STR (Stranded) | | |
| scriptions | AL VILLIAN ZEO CED DI ACIV DOC | | |
| Description | AL XHHW 750 STR BLACK PCS | | |
| nufacturer Information | | | |

Des

Mar

Brand Aluminum

Taxonomies, Classifications, and Categories

Category Description ALUM BUILDING WIRE

Packaging

| Carton | 1 | |
|-----------------|-------|--|
| Weight Per foot | 0.824 | |