

Eaton C440 electronic overload relay

XTOE020BCS

UPC:786685416410

Dimensions:

- Height: X
- Length: X
- Width: X

Warranties: No Data

Specifications:

- Contact Configuration: NO-NC
- Frame Size: 45 mm
- Mounting: Direct
- Overload Range: 4-20A
- Trip Type: Selectable - 10A, 10, 20, 30

Supporting documents:

- [C440 Electronic Overload Relay](#)
- [Eaton's Volume 5-Motor Control and Protection](#)
- [XTOE_B 3D Inventor](#)
- [XTOE_B AutoCAD 2D Footprint \(mm\)](#)
- [XTOE_B 2D PDF](#)
- [XTOE_B 3D Model Xchange](#)
- [XTOE_B AutoCAD 2D Footprint](#)
- [XTOE_B 2D Drawing Xchange](#)
- [XTOE/ZEB IEC Electronic Overload - Self Powered](#)
- [Eaton Specification Sheet - XTOE020BCS](#)

Certifications:

- IEC 60947
- UL Listed
- CSA Certified
- EN 60947

Product compliance:

- CE Marked



- ATEX Compliant
- RoHS Compliant

© 2016 Eaton. All rights reserved.

Eaton C440 electronic overload relay

XTOE020BCS

UPC:786685416410

Dimensions:

- Height: X
- Length: X
- Width: X

Warranties: No Data

Specifications:

- Contact Configuration: NO-NC
- Frame Size: 45 mm
- Mounting: Direct
- Overload Range: 4-20A
- Trip Type: Selectable - 10A, 10, 20, 30

Supporting documents:

- [C440 Electronic Overload Relay](#)
- [Eaton's Volume 5-Motor Control and Protection](#)
- [XTOE_B 3D Inventor](#)
- [XTOE_B AutoCAD 2D Footprint \(mm\)](#)
- [XTOE_B 2D PDF](#)
- [XTOE_B 3D Model Xchange](#)
- [XTOE_B AutoCAD 2D Footprint](#)
- [XTOE_B 2D Drawing Xchange](#)
- [XTOE/ZEB IEC Electronic Overload - Self Powered](#)
- [Eaton Specification Sheet - XTOE020BCS](#)

Certifications:

- IEC 60947
- UL Listed
- CSA Certified
- EN 60947

Product compliance:

- CE Marked



- ATEX Compliant
- RoHS Compliant

© 2016 Eaton. All rights reserved.