

Eaton XTOE020BCS

Catalog Number: XTOE020BCS

Eaton C440 electronic overload relay, XT IEC Electronic Overload Relay, 4-20A overload range, 45 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Selectable - 10A, 10, 20, 30 trip type



General specifications

Product Name	Catalog Number
Eaton C440 electronic overload relay	XTOE020BCS
UPC	Product Length/Depth
786685416410	1.77 in
Product Height	Product Width
4.33 in	1.42 in
Product Weight	Compliances
0.87 lb	CE Marked
	ATEX Compliant
	RoHS Compliant

Certifications

IEC 60947
UL Listed
CSA Certified
EN 60947

Product specifications

Overload range

4-20A

Type

Electronic overload relay

Frame size

45 mm

Mounting method

Direct

Contact configuration

NO, NC

Trip type

Selectable 10 A, class 10 ,20, 30

Resources

Brochures

[C440 Electronic Overload Relay](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTOE_B 3D Inventor](#)

[XTOE_B 2D PDF](#)

[XTOE_B 3D Model Xchange](#)

[XTOE_B AutoCAD 2D Footprint \(mm\)](#)

[XTOE_B AutoCAD 2D Footprint](#)

[XTOE_B 2D Drawing Xchange](#)

Installation instructions

[XTOE/ZEB IEC Electronic Overload - Self Powered](#)

Specifications and datasheets

[Eaton Specification Sheet - XTOE020BCS](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)

Eaton XTOE020BCS

Catalog Number: XTOE020BCS

Eaton C440 electronic overload relay, XT IEC Electronic Overload Relay, 4-20A overload range, 45 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Selectable - 10A, 10, 20, 30 trip type



General specifications

Product Name	Catalog Number
Eaton C440 electronic overload relay	XTOE020BCS
UPC	Product Length/Depth
786685416410	1.77 in
Product Height	Product Width
4.33 in	1.42 in
Product Weight	Compliances
0.87 lb	CE Marked
	ATEX Compliant
	RoHS Compliant

Certifications

IEC 60947
UL Listed
CSA Certified
EN 60947

Product specifications

Overload range

4-20A

Type

Electronic overload relay

Frame size

45 mm

Mounting method

Direct

Contact configuration

NO, NC

Trip type

Selectable 10 A, class 10 ,20, 30

Resources

Brochures

[C440 Electronic Overload Relay](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTOE_B 3D Inventor](#)

[XTOE_B 2D PDF](#)

[XTOE_B 3D Model Xchange](#)

[XTOE_B AutoCAD 2D Footprint \(mm\)](#)

[XTOE_B AutoCAD 2D Footprint](#)

[XTOE_B 2D Drawing Xchange](#)

Installation instructions

[XTOE/ZEB IEC Electronic Overload - Self Powered](#)

Specifications and datasheets

[Eaton Specification Sheet - XTOE020BCS](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)