

# Eaton XTCEXFAC04

Catalog Number: XTCEXFAC04

Eaton Contactor Accessory Auxiliary Contact, Four-pole, Screw terminals, 4NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton motor control auxiliary contact	XTCEXFAC04
<b>UPC</b>	<b>Product Length/Depth</b>
782116354559	1.5 in
<b>Product Height</b>	<b>Product Width</b>
1.3 in	1.5 in
<b>Product Weight</b>	<b>Compliances</b>
0.12 lb	CCC Marked
	CE Marked
	ATEX Compliant
<b>Certifications</b>	<b>Catalog Notes</b>
IEC 60947	Interlocked opposing contacts, to IEC/EN
EN 60947	60947-5-1 Annex L (positively driven),
UL Listed	within the auxiliary contact modules (not
CSA Certified	NOE and NCL contacts) and between
	the auxiliary contacts and built-in
	contacts of the XTRE control relays.



## defaultTaxonomyAttributeLabel

### Number Of Poles

Four-pole

### Type

Contactory Accessory - Auxiliary Contact

### Used with

XTRE control relays

### Terminals

Screw

### Contact configuration

4 NC

### Mounting method

Front

### Rated operational current

6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V

### Special features

Used with XTRE control relays

### Conventional thermal current

16A

### Quantity

5

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Specifications and datasheets

[Eaton Specification Sheet - XTCEXFAC04](#)

[Global Data Sheet - XTCEXFAC04](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)