# **Electrical Interlocking Bridge**

For Use with	Pkg. Qty. ①	Catalog Number
XTCE007B-XTCE015B	20	XTCEXLBB

# Star-Delta (Wye-Delta) Bridge

	For Use with	Pkg. Qty. ①	Catalog Number
XTCEXSDB	XTCE007B-XTCE015B	20	XTCEXSDBB ②
W			
XTCEXSDB_	XTCE080F-XTCE170G	1	XTCEXSDBG



Component part of star-delta link kit (XTCEXSDL\_). Commons the three phases on the line side of shorting contactor.

# Connector

	For Use with	Pkg. Qty. ①	Catalog Number
XTCEXCNC	XTCE007B-XTCE032C	50	XTCEXCNC



XTCEXCNG XTCE040D-XTCE170G 10 XTCEXCNG



	For Use with	Pkg. Qty. ①	Catalog Number
XTCEXPLKB	XTCE007B –XTCE015B	5	XTCEXPLKB
XTCEXPLK_	XTCE018C -XTCE032C	5	XTCEXPLKC
	XTCE040D -XTCE072D	1	XTCEXPLKD
	XTCE080F—XTCE170G	1	XTCEXPLKG
XTCEXPLKL185	XTCE185L	1	XTCEXPLKL185

Parallel Link 456

For using one contactor per phase. Each package comes with two links for line: load.

#### XTCEXTLA400

# **Terminal Lug Assembly**



For Use with	Pkg. Qty. ①	Catalog Number
XTCE185-XTCE225H	1	XTCEXTLA225A
XTCS250L-XTCS400M, XTCE250L-XTCE400M_	2	XTCEXTLA400

For connection of: round conductor, flexible and stranded, flat strip conductor, with control circuit terminal. See **Page V5-T1-97** for terminal capacities.

# XGKE-GE

# **Contactor Labels**



For Use with	Pkg. Qty.	Catalog Number
XTC	25	XGKE-GE ⑦

### Notes

- $^{\scriptsize \scriptsize \scriptsize (1)}$  Orders must be placed in multiples of package quantity listed.
- ② Frame B is toolless connection type.
- For mechanically arranging contactors in combinations. Distance between contactors is 0 mm.
- 4 Fourth pole can be broken off: four-pole:  $l_{th} = 60A$ ; three-pole:  $l_{th} = 50A$ .
- AC-1 current carrying capacity of the contactor increases by a factor of 2.5. For XTCEXPLKL185, one shroud
  is included for protection against accidental contact.
- © Protected against accidental contact in accordance with IEC 536.
- ① Quantity 1 equals one sheet. One sheet contains 240 labels.