Specifications

Eaton XTCR080F11A

Catalog Number: XTCR080F11A

Eaton XT IEC contactor, 80A, Top-mounted, 110 Vac 50 Hz, 120 Vac 60 Hz, 1NO-1NC, 80A, Frame F, 90 mm, 50-60 Hz, 7.5, 15/25, 30, 60, 75 hp (1/3PH @115, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVR

General specifications

Product Name
Eaton XT IEC contactor

Catalog Number
XTCR080F11A

UPC
782116356126

Product Length/Depth
9.5 in

Product Height
6 in

Product Width
6.5 in

Product Weight
4.7 lb

Compliances
CE Marked
RoHS Compliant

Certifications
UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes
Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

Powering Business Worldwide

Product specifications

Amperage Rating

80A

HP rating - max

7.5, 15/ 25, 30, 60, 75 hp (1/3PH @115,230/200,230,460,575 V)

Number Of Poles

Three-pole

Type

Full voltage reversing contactor

Frequency rating

50-60 Hz

Terminals

Screw terminals

Coil voltage

110-120 Vac, 50/60 Hz

Contact configuration

1 NO, 1 NC

Continuous ampere rating

80 A

Series

XT IEC

Operation

Reversing

Resources

Drawings

XTCR_F 2D Drawing Xchange

XTCR_F AutoCAD 2D Footprint

XTCR_F AutoCAD 2D Footprint (mm)

XTCR_F 3D Model Xchange

XTCR_F 2D PDF

XTCR_F 3D Inventor

Specifications and datasheets

Eaton Specification Sheet - XTCR080F11A

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia