

# Nylon Ring Terminal For 8 AWG

By Burndy Catalog # YAEV8CL1

Copper Lug, Ring Tongue, 1 Hole w/ Inspection Hole, 8 AWG, 1/4'' Stud, Insulated, Short Barrel, Tin Plated, 600 Volts Max.



## Application

For Very Demanding High Vibration Applications Encountered In Aircraft And Aboard Ships As Well As Motor Lead Applications In Hospitals, Industrials And Generating Plants

#### General

Color Code	Red
Connector Type	Ring Terminal
Die Index	435
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Insulation	Y
Insulation Type	Nylon
Material	Copper
Military Specification	MS25036
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Ring
Plated	Y
Plating Type	Tin
Sub Brand	INSULUG
Trade Name	INSULUG™
Туре	YAEV-L, Heavy Duty
UPC	781810027745
UPC 12 Digit	7818100277455

#### Dimensions

Dimension - B Length fraction	9/25 in
Dimension - B Length inch	0.36 in
Dimension - Bolt Size fraction	1/4
Dimension - Length Overall inch	1.47 in
Dimension - N inch	0.23 in
Dimension - P inch	0.13 in
Dimension - Pad Width inch	0.46 in
Dimension - Stud Size inch	1/4
Dimension - Z inch	0.32 in

## **Electrical Ratings**

Voltage - Maximum

600 V

## **Conductor Related**

Conductor - Copper Str Aircraft Size	AN 8
Conductor - Copper Str Aircraft Size Range	AN 8
Conductor - Copper Str Size	8
Conductor - Copper Str Size Range	8
Conductor Size	8 AWG
Conductor Type	CU C Solid-Size
	• CU C Str-Size

#### **Certifications and Compliance**

Certification - CSA Approved Industry Standard(s)	No • UL486
	<ul> <li>Military Specified (Mil- Spec)</li> </ul>
Standards - Industry Standards Met	• UL486
	<ul> <li>Military Specified (Mil- Spec)</li> </ul>
Standards - RoHS Compliance Status	СМ
UL Listed	Yes
Logistics	
Carton Quantity	200
Minimum Pack Quantity	200

Minimum Pack Quantity	200
Pallet Quantity	99999

# **Product Assets**

3D Models - YAEV8CL1\_MODEL-IGES 3D Models - YAEV8CL1\_MODEL-PDF 3D Models - YAEV8CL1\_MODEL-STEP Sales Drawings - 50094163 Technical Solutions - BURNDY\_YAEV8CL1\_Specsheet

