

Uninsulated Ring Terminal For 4 AWG

By Burndy Catalog # YAV4CL4

Copper Compression Lug, Ring Tongue, 1 Hole w/ Inspection Window, AN 4 Flex, 5/16" Stud, Short Barrel, Electro-Tin Plated.



Application

For Use On Type AN Aircraft Cable, Extra Flexible Conductors And Commercial (Code) Conductors, Industrials, Hospitals, Electric Utilities, Marine, Computers, And Other Equipment Subject To Vibration Or Requiring Dependable Electrical Performance

General

Connector Type Ring Terminal Die Index 40 **EU RoHS Indicator** Ves Feature - Barrel Style Chamfered Skived Feature - Barrel Type Standard Material Copper Material Composition DLP Copper · Tin Plating MS20659 Military Specification Physical Attribute - Number of 1

Holes Physical Attribute - Tongue Ring

Type

Plated

Plating Type

Tin - Electro Plated

Straight

Sub Brand **HYLUG** Trade Name HYLUG™ Type Ring Tongue UPC 781810025574

Dimensions

Dimension - B Length fraction 1/2 in Dimension - B Length inch 0.47 in Dimension - Bolt Hole Size 0.33 in inch 5/16 Dimension - Bolt Size fraction Dimension - Length Overall 1.48 in inch Dimension - N inch 0.31 in Dimension - Pad Width inch 0.63 in Dimension - Strip Length inch 1/2 Dimension - Stud Size inch 5/16 in 0.33 in Dimension - Z inch

Physical Attribute - Tongue

Angle

Conductor Related

Conductor - Copper Str AN 4 Aircraft Size

Conductor - Copper Str Size

Conductor - Copper Str Size

Range

Conductor Size 4 AWG

• CU C Solid-Size Conductor Type

• CU C Str-Size

4 AWG

UL486

Certifications and Compliance

Certification - CSA Approved Yes Certification - ETL Nο Certification - UL Recognized Nο Certification - cULus Nο

Industry Standard(s) UL467

> · Military Specified (Mil-Spec)

Standards - Industry

Standards Met

Standards - RoHS Compliance

Status

UL Listed Yes

Logistics

200 Carton Quantity Minimum Pack Quantity 200 Pallet Quantity 79200

Product Assets

Catalogs - Full Line BURNDY Catalog Sales Drawings - 50094161 E

Technical Solutions - BURNDY_YAV4CL4_Specsheet





