

YAV8CL1, Cu Compression, 1-Hole, 1/4" Stud, Standard Barrel, 8 Flex

By Burndy Catalog # YAV8CL1

Copper Compression Lug, Ring Tongue, 1 Hole w/ Inspection Hole, AN-8 Flex, $1\!/\!4''$ Stud, Short Barrel, Tin Plated.



Application

For Use On Type AN Aircraft Cable, Extra Flexible Conductors And Commercial (Code) Conductors, Industrials, Hospitals, Electric Utilities, Marine, Computers, And Other Equipment Subject To Vibration Or Requiring Dependable Electrical Performance

General

Connector Type	Ring Terminal
Die Index	38
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Material	Copper
Material Composition	DLP Copper
	• Tin Plating
Military Specification	MS20659
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Ring
Plated	Υ
Plating Type	Tin - Electro Plated
Sub Brand	HYLUG
Trade Name	HYLUG™
Туре	Ring Tongue
UPC	781810025079
Dimensions	
Dimension - B Length inch	0.405 in

Dimension - B Length inch	0.405 ir
Dimension - Bolt Size fraction	1/4
Dimension - Length Overall inch	1.22 in
Dimension - N inch	0.25 in
Dimension - Outside Diameter inch	0.27 in
Dimension - Pad Width inch	0.46 in
Dimension - Stud Size inch	1/4

Conductor Related

Conductor - Copper Str Aircraft Size	AN-8
Conductor - Copper Str Size	8 AWG
Conductor - Copper Str Size Range	8 AWG
Conductor Size	8 AWG
Conductor Type	CU C Solid-Size
	• CU C Str-Size

Certifications and Compliance

Certification - CSA Approved Certification - ETL Certification - UL Recognized Certification - cULus Industry Standard(s)	Yes No No • UL467 • Military Specified (Mil- Spec)	
Standards - Industry Standards Met	UL467Military Specified (Mil- Spec)	
Standards - RoHS Compliance Status UL Listed	CM Yes	
Logistics		
Carton Quantity Minimum Pack Quantity Pallet Quantity	200 200 99999	
Product Assets		
3D Models - YAV8CL1_MODEL-PDF		

3D Models - YAV8CL1_MODEL-IGES 3D Models - YAV8CL1_MODEL-STEP Sales Drawings - 50094161_E Technical Solutions - BURNDY_YAV8CL1_Specsheet

