


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





LPJ80SP 80A 600V TD Dual Elem Class J Fuse

Bussmann Fuses

Catalog Number	LPJ80SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series LPJ Fuse, 600 V, 80 A, 300 Ka
Weight per unit	0.3000 (lbs/each)
Product Category	Dual Element

Features

amperage rating	80 Amp
class	J
connection	Bolted Blade End X Bolted Blade End
dimensions	4.6300 IN X 1.1300 IN X 1.1300 IN
element	Dual
interrupt rating	300000 Amp (RMS Symmetrical UL), 100000 Amp (DC)
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc

Dimensions and Weight

Size 1.13 In Diameter X 4.63 In Length

Descriptions

Description	80A 600V TD DUAL ELEM CLASS J FUSE
extra long description	BUSS LPJ-80SP LOW-PEAK CLASS J T/D
Features	Bussmann's UL Class J fuse products extend both our Low-Peak family of products with our LPJ_SP and LPJ_SPI dual-element, time-delay fuses as well as our Limitron line offering fast-acting JKS fuses. The LPJ fuses provide industry leading 300,000 amp interrupting rating at 600Vac RMS Sym and 100kA Vdc while delivering a minimum of 10 seconds of 500 percent rated current ride-through performance which is ideal for sizing of high inrush loads. The LPJ products are available with optional permanent replace fu
Long Description	Eaton Bussmann series LPJ fuse, 600 V, 80 A, 300 kA
Product Type	Low-Peak Class J T/D

Manufacturer Information

Brand	Eaton
GTIN	00051712523387
Manufacturers Part Number	LPJ-80SP
UPC	051712523387



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	Fuses & Fuse Accessories	
Туре	FUSE	
Packaging Carton	1	
Weight Per each	0.3	
Uses, Certifications, and Standards		
Application	Ind Facilities & Factories - Facility: Safety and Security Systems	
standard	UL Listed ,CSA Certified,RoHS Compliant	